



NOTES:

1. CONCRETE CURB SHALL NOT ENCR OACH INTO PUBLIC RIGHT-OF-WAY AND SHALL BE FLUSH AT BACK OF WALK.
2. COMMERCIAL DRIVEWAY SHALL BE INSTALLED IN ZONES DESIGNATED COMMERCIAL, INDUSTRIAL, AND RESIDENTIAL WITH 4 UNITS OR MORE.
3. 18\"/>
4. JOINT/SCORE MARK TABLE:

DRIVEWAY WIDTH		WEAKENED PLANE JOINT		SCORE MARKS	
MIN.	MAX.	NO. OF JOINTS	LOCATION POINT	NO. OF MARKS	LOCATION POINT
24'	30'	2	1/3, 2/3	3	1/6, 1/2, 5/6
>30'	40'	3	1/4, 1/2, 3/4	4	1/8, 3/8, 5/8, 7/8
>40'	50'	4	1/5, 2/5, 3/5, 4/5	5	1/10, 3/10, 1/2, 7/10, 9/10

SCORE MARK REQUIRED AT DRIVEWAY SLOPE BREAK PARALLEL TO EXISTING FACE OF CURB



DRAWN BY: M. LEE

CHECKED BY: S. THACH

APPROVED BY: T. SUPAN

DATE: JANUARY 2007

COMMERCIAL DRIVEWAY WITH/ WITHOUT SEPARATED SIDEWALK

CITY OF SANTA CLARA

ST-4

PAGE: 4